



## Spirobank II<sup>®</sup> Basic

Low cost handheld diagnostic Spirometer with interpretation. Measures basic parameters. PC connectivity via USB.

The Spirobank II<sup>®</sup> Basic is a handheld, portable diagnostic spirometer designed for use in environments where it's only necessary to take basic measurements of the main spirometric parameters.

Its pocket size design with rechargeable long-life battery makes it ideal for use in situations where remote testing is required. The user interface is fast and intuitive to operate with an icon-based navigation menu on a backlit, high resolution display. It can be used as a "stand-alone" with onboard memory that is capable of storing up to 10,000 test results. It can also connect to a PC via USB allowing for real-time spirometry testing, and downloading of test results stored on the device using the free MIR WinspiroPRO<sup>®</sup> PC Software.

The Spirobank II<sup>®</sup> Basic measures FVC, FEV1, FEV1%, PEF, FEF25-75, FET, Extrap. Volume, Lung Age, VC, IVC, IC, ERV and PRE and POST Bronchodilator comparison. Results are previewed on the display following a test, with a flow/volume graph in addition to the patient's actual spirometry readings for immediate assessment. It also features a traffic light health indicator for easy interpretation of results.

### Re-usable and disposable consumable options

The Spirobank II<sup>®</sup> Basic can be used with both re-usable and single-use disposable turbines. Re-usable turbines are used with standard adult one-way valve mouthpieces. The single-use disposable turbines have a pre-connected mouthpiece and are individually factory calibrated and packaged.

### KEY FEATURES

- **Easy to use handheld spirometer**  
Navigate easily through the icon-based menus on a clear, high resolution screen
- **Measures main spirometric parameters**  
Perfect for simple spirometry testing
- **Traffic light health indicator**  
A visual way to easily interpret test results
- **Large memory storage**  
Store up to 10,000 tests
- **USB connectivity to PC**  
Download results stored on the device and conduct real-time spirometry using WinspiroPRO<sup>®</sup> PC software.
- **Built in rechargeable battery**



## MIR Spirobank II® Basic

TECHNICAL SPECIFICATIONS	
Device category	Diagnostic spirometer
Spirometry parameters	FVC, VC, IVC, IC, ERV, FEV1, FEV1%, PEF, FEF 25-75, FET, EVOL
Flow measurement	± 16 L/s
Volume accuracy	± 3% or 50 mL
Flow accuracy	± 5% or 200 mL/s
Temperature sensor	Semiconductor (0-45°C), automatic BTPS conversion
Data transmission	USB
Memory storage	Approx. 10,000 tests
Power	3.7 V, 110 mA lithium battery - USB rechargeable
Display	160 x 80 pixel with 6-key membrane keyboard
Dimensions	160x55x25 mm
Weight	140 g (with battery)

## Ordering Information

PART NUMBER	DESCRIPTION
MR-911021E1	MIR Spirobank II® Basic with re-usable turbine
MR-911021E2	MIR Spirobank II® Basic with 100 x disposable turbine
MR-910002	Replacement re-usable turbine
MR-910004	Disposable turbines (Box of 50)
881002	One-way valve adult mouthpieces for re-usable turbine (Box of 200)

© 1997-2018. Intermedical (UK) Limited. All rights reserved.

All information, specifications and illustrations contained in this document are based on the latest product information available at the time of publication. Errors and omissions excepted. Intermedical (UK) Limited reserves the right to change specifications and design at any time without prior notice.



Exclusive UK distributor

